

PORTABLE POWER DISTRIBUTION UNIT



OUR PORTABLE POWER DISTRIBUTION UNIT

Designed to meet various job site temporary power connection requirements, the Easter-Owens power distribution unit is portable and completely self-contained with internal wiring connections from breaker to receptacle.

STANDARD FEATURES

75KVA transformer.

480 VAC 12 circuit primary, 225A main circuit breaker 3P/3W with main Meltric inlets.

480 VAC load receptacles: QTY 2, 50A, 3P/4W Hubbell CS8169.

Other brands of main inlet connectors and load receptacles available upon request.

208Y/120 VAC load receptacles:

- QTY 6, 50A, 3P/4W Hubbell CS6369
- QTY 1, 50A, 4P/5W Hubbell CS8169
- QTY 4, 50A, 3P/4W Hubbell CS8169

Integral transformer fan with thermostat for high ambient temperature, job site conditions.

12-gauge cold rolled steel construction.

Type 3R construction standard.

Lifting eyes and fork lift pockets for easy job site movement.

Hinged door on each end of unit with flush, 2-pt handle.

Pad lock hasp and staple.

Powder coated RAL9003-White.

Custom colors available. Shipping weight approximately 1300lbs./590kg.

Drawings available, please consult factory.



OPTIONS

Other environmentally rated enclosures are available.

Custom paint colors.

Custom power configurations.

Refurbishing and maintenance on unit available as required.

APPROVALS

UL listed.



HEADQUARTERS

6692 Fig Street
Arvada, Co 80004

Phone: 303.431.0111
Fax: 303.424.2040

EASTER-OWENS.COM

CONTACT US FOR PROJECT
REFERENCE INFORMATION



CALL TOLL FREE: **1.866.204.3707**